



energie atomique • énergies alternatives

ICOPS 2011 SOFE



Chicago, Illinois

38th International Conference on Plasma Science and 24th Symposium on Fusion Engineering

June 26-30, 2011 | Chicago, Illinois

Tore Supra Status and Future Plans

J. Bucalossi on behalf of Tore Supra Team
IRFM, CEA Cadarache
13108 Saint Paul lez Durance, France



A tokamak fully equipped for Long Pulse Operation



- Superconducting toroidal magnetic field: **up to 4T**
- High heat flux carbon plasma facing components: **10MW/m²**
- Actively cooled first wall (SS panels): up to **10MW** extracted in steady-state
- Strong H&CD capability: **15MW of RF power**
- Fully non inductive operation: **1GJ with ~400s steady state plasmas**
- **ITER relevant particle fluence** within reduced time of operation

Outline



énergie atomique • énergies alternatives

- **Tore Supra Status**
 - > New LHCD system for CW operation
 - > ITER startup experiments
 - > Disruption and runaway studies
 - > Development of a generic multipurpose flight simulator
- **Tore Supra looking WEST for the second ITER divertor**
 - > Motivations for the evolution of Tore Supra
 - > Implementing a W Divertor into Tore Supra
 - > Project schedule
- **Summary**

New LHCD system for CW operation

cea

energie atomique • energies altern



- Complete renewal of the power transmitter, including **16 new klystrons TH2103C** (Thalès Electron Devices)

L Delpech et al, RF conf. 2011

- ITER-relevant **PAM antenna** (Passive-Active Multijunction)

> The PAM is foreseen for ITER LHCD launcher

D Guilhem et al, FED 2011





- Extend domain of long pulse operation for Tore Supra: **higher density and plasma current**

ITER power relevant density achieved over long pulses



- **2.75MW** (25MW/m²) coupled with PAM for 78 seconds

energie atomique • energies alternatives



- **Low RC** at large plasma-launcher gap (n_e at launcher $> n_{co}$)
- **Efficient cooling**: waveguides and side protections remain below 270°C
- High RF power density **25MW/m² scales to 33MW/m² for ITER 5GHz**



A Ekedahl et al, RF conf. 2011

Fully non inductive plasmas with the PAM launcher



energie atomique • energies alternatives

- **Zero loop voltage maintained over 50s with 2.2MW LHCD**



A Ekedahl et al, Nucl. Fusion **50** (2010)


- Double feedback control loops to maintain I_p constant and $V_{\text{loop}} = 0$
- **CD efficiency: $\eta_{\text{LHCD}} \sim 0.75 \times 10^{19} \text{ A/W/m}^2$** (bootstrap current fraction $\sim 10\%$)
- Similar to Full Active Multijunction antennas (cf GJ-discharges)

Extended domain of steady-state operation



energie atomique • energies alternatives

- Using both LHCD antennas together: **4.5MW/150s** readily obtained (650MJ injected energy)
- Opens new operation space (n_e , I_p) for **long pulse operation**




- **High energy with LHCD**
 - > 5MW LHCD 400s
- **High energy with ICRH**
 - > 4MW LHCD + 3MW ICRH 200s
- **High power discharges**
 - > 6MW LHCD + 9MW ICRH 30s

ITER start-up experiments



energie atomique • energies alternatives

- **The ITER blanket/first wall will now be used as a start-up and ramp-down limiter**
 - > Two original dedicated outboard start-up limiters eliminated, change accepted into the ITER Baseline during Configuration Control Board 047 on 10/05/2010



Tore Supra configuration well adapted to start-up studies



- **Six mobile outboard limiters:**
 - > 1 semi-inertially cooled limiter (CFC tiles bolted on Cu cooling channels)
 - > 5 RF antennas with actively cooled side protection tiles (CFC tiles brazed to Cu-Cr-Zr cooling channels → 20MW/m²)
- **Six fixed inboard limiters:**
 - > CFC tiles bolted on Cu cooling channels

HFS contact results in broader λ_q and lower $q_{||}$



energie atomique • energies alternatives

- **For identical core plasmas**, the probe can penetrate a few cm inside the LCFS for HFS contact, but cannot even reach it for LFS contact!




J. Gunn et al, ITPA 2011

Large scatter on ITER scaling law prediction




energie atomique • energies alternatives

- Tore Supra measurements are **not well correlated with ITER scaling law**, but they do follow a clear empirical dependency with ohmic power



J. Gunn et al, ITPA 2011



$$\text{ITER} : \lambda_q = \left(1 \pm \frac{1}{3}\right) 3.6 \times 10^{-4} R^2 P_{SOL}^{-0.8} q_a^{0.5} n_e^{0.9} Z_{eff}^{0.6}$$

$$\text{TS} : \lambda_q = \left(1 \pm \frac{1}{10}\right) 0.025 P_{\Omega}^{-0.7}$$





New reciprocating probes installed in 2011



energie atomique • energies alternatives

- Two magnetically driven reciprocating probes were installed on the **modular outboard limiter** during the winter 2011 shutdown



- > Real time feedback control of the probe position has been successfully implemented (probe velocity controlled by coil current with 1 ms time resolution, position measured with respect to real LCFS position)


Disruptions and runaway studies



energie atomique • energies alternatives

- On Tore Supra, **long lasting RE plateau (multi seconds!!!)** can develop following disruptions

60kA runaway electron beam striking CFC wall in Tore Supra



- > RE well confined
- > Accelerated during current quench (CQ) up to relativistic energy (10-20MeV)
- > Very small pitch angle
- > RE loss on a small wall area
- > huge energy density deposits ($10\text{MJ/m}^2 \sim 1\text{GW/m}^2$) and deep penetration inside the PFCs (few cm)

Control of the RE plateau regime




energie atomique • energies alternatives


- Current carried by **relativistic electrons in the core of a cold plasma**

RE plateau with position & current control

TS#46082



- > High resistivity (twice ohmic values)
- > Large internal inductance (twice pre disruption values) → **very peaked current profile**
- > Slow decrease of li on flattop → flattening of the current profile (collisions effect?)



F Saint-Laurent et al, EPS 2011






Two types of events observed during RE plateau



- **Direct losses** onto the wall associated with current drops

- **Radiative events** → key for RE heat load mitigation?

energie atomique • energies alternatives



New ultra fast gas injector installed in 2011



energie atomique • energies alternatives

- **Rupture disk based high pressure injector**

- > No delay between trigger and HT pulse
- > HT pulse delivered in less than $300\mu\text{s}$
- > Gas delivered in less than $500\mu\text{s}$
- > Filling pressure 100-130bars

- **Injections feasible during the current quench**


- **Expected effect: spread RE onto the first wall hindering beam formation**

- > Gas jet penetration up to $q=2$
- > Destabilization of MHD equilibrium
- > Ergodisation of field lines

Under ITER contract




S. Putvinski et al, IAEA 2010



A generic flight simulator for long pulse operation




energie atomique • energies alternatives



Empirical methods not applicable for new tokamak challenges →
Tool needed to optimize tokamak operation

Interfacing with the European simulation platform



P Moreau et al, SOFT 2010

Outline



energie atomique • energies alternatives

- **Tore Supra Status**
 - > Installation of an ITER relevant LH antenna
 - > Experimental results with the new LH antenna
 - > ITER startup experiments
 - > Disruption and runaway studies
 - > Development of a generic multipurpose flight simulator
- **Tore Supra looking WEST for the second ITER divertor**
 - > Motivations for the evolution of Tore Supra
 - > Implementing a W Divertor into Tore Supra
 - > Project schedule
- **Summary**



Motivations for the evolution of Tore Supra



energie atomique • énergies alternatives

- Following ITER recent decision to go to **full tungsten divertor** for its nuclear phase, it is proposed to use Tore Supra facility to **test ITER divertor technology in tokamak environment** in order to **reduce the risks for ITER**

Carbon	Tungsten	Challenges for tungsten components
Heat resistant, sublimates	Heat resistant, melts	Component integrity Impact on subsequent ITER operation
Full technology industrial development for 20 years	Recent technology development, never tested in fusion devices	Delay for ITER construction
Used in most devices (1980-2010) Basis for ITER Physics and operation	Experience restricted to ASDEX upgrade (progressive use from 1996 to now)	New physics and operation basis to consolidate
A few % plasma pollution acceptable	Plasma pollution acceptable $\ll 10^{-4}$	Plasma contamination impact on ITER fusion performance


Turning Tore Supra into a divertor configuration



energie atomique • energies alternatives

- The WEST project: **W** Environment in **S**teady State **T**okamak
- The transformation from the present circular limiter geometry to the required X-point configuration will be achieved by installing a set of water cooled **copper poloidal coils inside the lower and upper parts of the vacuum vessel**

From the Tore Supra present configuration...



... to the WEST configuration


A new steady state divertor tokamak




$B_T = 3.7 \text{ T}$

$I_p \leq 1 \text{ MA}$ ($q_{95}=2.5$)

R: 2.5 m
a: 0.5 m
A: 5-6
 κ : 1.3-1.8
 δ : 0.5-0.6
 V_p : 15 m³



- Lower, upper, double x-point configurations
- Stabilizing plates for vertical control
- **ITER W monoblock at targets**



W monoblock design will be closely based on that currently envisaged for ITER

- ITER First Wall (W coated) at upper divertor targets
- Pumping baffle for plasma density control
- Divertor coils reference design for **steady-state operation at $I_p \leq 0.8 \text{ MA}$**


J Bucalossi et al, FED 2011

With relevant steady-state heat fluxes



energie atomique • energies alternatives

- **LHCD** (10MW) **7MW-1000s** (CIMES project)
- **ICRH** (12MW) **9MW-40s/6MW-60s**, **ELM compatibility** (3dB couplers), **3MW-1000s**
- **Heat flux controlled by the X-point height** (flux expansion)
 - > From **7 to 40 MW/m²** (for $P_{\text{SOL}}=10\text{MW}$ and $\lambda_q=2.5\text{mm}$)
- **W compatibility**
 - > Cf. AUG experiments
 - > SOLPS/DIVIMP
 - > ICRH central heating
- **Type I ELMy H mode**
 - > $P_{\text{L-H}} \leq 5 \text{ MW}$
 - > $W_{\text{ELM}} \leq 50\text{kJ}$
- **PFC survey**
 - > T_{surf} monitoring (IR)
 - > Erosion (W spectroscopy)
 - > Visual inspection (AIA robot)




Divertor modular design for easier PFC testing




energie atomique • energies alternatives

L Doceul et al, FED 2011



Plug and play 30° sector



Hydraulic connection

WEST plasma scenarios for PFC testing



energie atomique • energies alternatives

- The WEST configuration will provide the capability to run **long pulses in the high confinement regime (H mode)** foreseen for ITER, and **test plasma facing components under realistic plasma conditions**

SCENARIO	HIGH POWER	STANDARD	HIGH FLUENCE
Plasma current	0.8 MA	0.6 MA	0.5 MA
Toroidal magnetic field	3.7 T	3.7 T	3.7 T
Plasma density	$9 \cdot 10^{19} \text{m}^{-3}$	$6 \cdot 10^{19} \text{m}^{-3}$	$4 \cdot 10^{19} \text{m}^{-3}$
Total radiofrequency heating power	15 MW	12 MW	10 MW
Lower Hybrid Current Drive	6 MW	6 MW	7 MW
Ion Cyclotron Resonance Heating	9 MW	6 MW	3 MW
Plasma current flat-top duration	30 s	60 s	1000 s
Expected heat load*	6 MW/m²	11 MW/m²	15 MW/m²
Expected ELM energy	51 kJ	32 kJ	26 kJ
Expected ELM frequency	59 Hz	76 Hz	77 Hz
Expected ELM load	40 kJ/m ²	52 kJ/m ²	74 kJ/m ²
Expected operation time to reach one ITER pulse particle fluence	~6 months	~2 months	~few days


*Assuming $\lambda_q = 5 \text{ mm}$

Bringing answer in time for ITER



energie atomique • energies alternatives

- The WEST project would **deliver critical information** on:
 - “1) manufacturing failure modes, 2) repairing processes, 3) acceptance criteria, 4) leading edge issues, 5) operation with solidified tungsten melted surfaces, 6) behaviour of cracks under combined thermal and electromagnetic loads, 7) relevant diagnostics for tungsten armoured actively cooled components, etc.”*
- Operation of Tore Supra in the WEST configuration can start **about 5 years** after launching the preliminary design activities ~ foreseen minimum time required for the detailed design and **manufacturing of actively cooled W PFC**



*Assessment by an international panel of experts including IO members (December 2011)

Summary



energie atomique • energies alternatives

- **Tore Supra is currently addressing some crucial issues for ITER operation:**
 - > ITER relevant LHCD antenna concept validated
 - > LHCD upgrade will extend domain of steady state operation
 - > ITER startup experiments raised issues on heat loads prediction
 - > Progress on runaway electrons characterization and control
 - > New tools in development to optimize long pulse operation
- **With the WEST project proposal and the implementation of an actively cooled tungsten divertor, Tore Supra will offer the key capability to test ITER HHF PFC technology in real plasma conditions**
- **And thus bring answers in a timely manner for the 2nd divertor foreseen for the nuclear phase of ITER (in complement to JET and ASDEX Upgrade W programmes)**

Preliminary design activities have been launched and international partners are invited to participate to the project and scientific exploitation



energie atomique • energies alternatives

ANNEXE



24th SOFE, June 26-30, 2011, Chicago, Illinois

J. Bucalossi on behalf of Tore Supra Team



2727/26



WEST structure and casing



energie atomique • énergies alternatives



WEST steady state scenario



energie atomique • energies alternatives

- **LHCD @ mid-radius**
- Steady-state wide q-profile reversal
- $P_{ICRH} = 9$ MW (sensitivity: a minimum of 6 MW is required)
- $P_{LH} = 3.7$ MW \rightarrow margin remains on P_{LH}
- 85 % electron heating; $\eta_{LH} = 1.1 \cdot 10^{19}$ A/W/m²
- **100% non-inductive, 40 % bootstrap** and 60 % LHCD; $\beta_N \sim 1.7$; $\beta_P \sim 3$; $\rho^* = 4 \cdot 10^{-3}$
- **Very similar q-profile and LH deposition as foreseen for ITER steady-state scenario**

Typical ray trajectory (only 1 ray shown)

